MATERIAL SAFETY DATA SHEET

1. PRODUCT IDENTIFICATION AND COMPANY

Product Name SN 150 N

Product Type Base oil (Group2)

Company PT. PACIFIC LUBRITAMA INDONESIA

Jl. Raya Bojonegara KM 6, Desa Bojonegar Serang

Banten - Indonesia. 42454

Tel: (62-254) 5750555 Fax: (62-254) 5750333

2. COMPOSITION

Mineral Oil Content 100 %.

3. HAZARDS IDENTIFICATION

Human Health

Hazards

Product is not hazardous.

Eye Contact Slightly irritant.

Skin Contact Prolonged or repeated contact may irritate skin.

Inhalation Repeated and prolonged over-exposure to oil mists may cause

irritation or discomfort.

Ingestion Minimal toxicity.

Safety Hazards Not classified as flammable but will burn.

Environmental

Hazards

Not readily biodegradable.

PT. PACIFIC LUBRITAMA INDONESIA ISO 9001: 2008 Certificate No. JKT 0500213

4. FIRST AID

Eye Contact Flush eyes with large amount of water until irritation subsides. If

irritation persists, get medical attention.

Skin Contact Flush with large amount of water; use soap if available. Remove

contaminated clothing. If irritation persists, get medical attention.

Inhalation Remove to fresh air. If rapid recovery does not occur, get medical

attention.

Ingestion Do not induce vomiting. If rapid recovery does not occur, get

medical attention.

5. FIRE SAFETY

Flash Point >200 °C.

Flammable Limits LEL 1.0.

UEL 6.0.

Autoignition Temp >250°C.

Specific Hazards Not classified as flammable but will burn. Hazardous combustion

products may include carbon monoxide, oxides of sulphur, and

unidentified organic and inorganic compounds.

Fire Fighting Use dry chemical, foam or carbon dioxide to extinguish fire.

Water may cause splattering or frothing. Use water to cool and protect fire-exposed material. Wear protective equipment during fire

fighting.

6. ACCIDENTAL RELEASE MEASURES

Clean-up Procedure Stop the source of leak or release and contain spill if possible.

Cover spill with generous amount of inert absorbent material such as sand or earth. Sweep up and remove to suitable, clearly marked

sand of earth. Sweep up and remove to suitable, clearly h

containers for disposal in accordance with local

regulations. Scrub contaminated area with detergent and water. Pick up liquid with additional absorbent material and dispose as above. Wear

proper protective equipment during clean-up.

7. HANDLING AND STORAGE

Handling Handling temperatures should not exceed 70oC. Wear proper

safety protective equipment. Wash hands thoroughly after handling. Water contamination and spillage should be avoided.

Storage Storage temperatures should be maintained between 0 to 50oC.

Odorous and toxic fumes may be evolved from decomposition of

product if stored above the safe temperature.

8. EXPOSURE CONTROL/PERSONAL PROTECTION

Exposure Limits Threshold Limit Values for oil mist is recommended to be

controlled at 5 mg/m3 or lower for exposure of 8 hours daily.

Ventilation Use exhaust ventilation to keep below exposure limits.

Eye Protection Wear safety glasses or face shields if splashing is likely to occur.

Skin Protection Avoid repeated and prolonged contact with product. Use oil

resistant gloves.

Respiratory

Protection

Not normally required unless in confined space.

Body Protection Use proper protective equipment to avoid contact. Wear PVC

apron if splashes are likely to occur.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State Liquid. Colour Clear

Odour Characteristic mineral oil.

Vapour Pressure <0.5 Pa at 20°C.
Density 0.8560 g/cm3 at 15°C

Kinematic Viscosity @ 40°C

Kinematic Viscosity @ 100°C

Pour Point

Flash Point

pH of undiluted product

Auto-ignition temperature

Solubility in water

29.86 cSt.

5.265 cSt.

-18 °C.

Not available.

>250°C.

Negligible.

10. STABILITY AND REACTIVITY

Stability Product is stable under normal use conditions.

Thermal Carbon monoxide, carbon dioxide, oxides of sulphur and Decomposition nitrogen and organic and inorganic compound may evolve

when subject to heat or combustion.

Hazardous Will not occur under normal conditions.

Polymerisation

Incompatible Strong oxidizing agents. Strong acids. Materials



PT. PACIFIC LUBRITAMA INDONESIA ISO 9001: 2008 Certificate No. JKT 0500213

TOXICOLOGICAL INFORMATION

Basis

No toxicological data is available for this product. Information is provided based on the additives, other components and base stock

used.

Acute Exposure

- Oral

LD 50 expected to be above 2000 mg/kg.

Acute Exposure

- Skin

LD 50 expected to be above 2000 mg/kg.

Inhalation Repeated or prolonged exposure to oil mists may cause irritation.

Eye Irritation Slightly irritant.

Skin Irritation Not a skin irritant unless repeated or prolonged contact.

Respiratory

Irritation

Slight irritant.

Carcinogenicity No data to suggest that product is carcinogenic.

Mutagenicity No data to suggest that product is mutagenic.

Other Information Brief contact with used oil is not expected to have serious effect

in humans if the oil is removed thoroughly by washing with soap and

water.

The concentration of such impurities will depend on use and they present risks to health and the environment on disposal. All used oils should be handled with caution and skin contact should be avoided.

PT. PACIFIC LUBRITAMA INDONESIA ISO 9001: 2008 Certificate No. JKT 0500213

12. ECOLOGICAL INFORMATION

Basis No ecological data is available for this product. Information is

provided based on the additives, other components and base stock

used.

Mobility Liquid under most environmental conditions. Floats on water. It

is absorbed by soil and will not be mobile.

Persistence/ Not readily biodegradable. Major constituents are expected to

Degradability be inherently biodegradable, but the product contains components that

may persist in the environment.

Bioaccumulation Has the potential to bioaccumulate.

Ecotoxicity Poor soluble mixture. Practically non-toxic to aquatic organisms.

May cause physical fouling of aquatic organisms.

13. DISPOSAL CONSIDERATION

Product Disposal Used or waste oil should be recycled or disposed off in conformity to

local disposal regulations. Contact local authorities for approved

disposal contractor.

Container Disposal Empty drums should be completely drained and sent to a drum

reconditioner or properly disposed of. Non-reusable small

containers should be recycled or disposed of. Ensure conformity to

local disposal regulations.

14. TRANSPORT INFORMATION

General Information Not dangerous for conveyance under UN, IMO, ADR/RID and

IATA/ICAO codes.

15.	REGULATORY INFORMATION	
	Not Applicable.	
16.	OTHER INFORMATION	

The above information is based on data of which we are aware and is believed to be correct as of the date hereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose. Therefore, no warranty either expressed or implied of merchantability or fitness for particular purpose is made with respect to the product or the information contained herein.